





C-PVC FITTINGS


Description	Part No.	Size (Inch)	SP	MC
Coupling 	213206	1/2	20	500
	213207	3/4	20	260


Description	Part No.	Size (Inch)	SP	MC
Pipe Clamp 	212806	1/2	25	625
	212807	3/4	25	625

Description	Part No.	Size (Inch)	SP	MC
45 Deg. Ell 	213806	1/2	20	500
	213807	3/4	20	260


Description	Part No.	Size (Inch)	SP	MC
End Cap 	214606	1/2	10	500
	214607	3/4	10	250

Description	Part No.	Size (Inch)	SP	MC
90 Deg ELL 	214260	1/2	20	500
	214267	3/4	20	260

Description	Part No.	Size (Inch)	SP	MC
Male Adaptor 	210806	1/2	20	500
	210807	3/4	10	250

Description	Part No.	Size (Inch)	SP	MC
Tee 	216606	1/2	20	500
	216607	3/4	20	260

Description	Part No.	Size (Inch)	SP	MC
Female Adaptor 	210406	1/2	20	500
	210407	3/4	10	250

Description	Part No.	Size (Inch)	SP	MC
Reducing Bush 	212411	3/4 x 1/2	10	500

TEMPERATURE VS. PRESSURE

C-PVC pipe and fittings are manufactured in copertube sizes (SDR11) to conform to ASTM D - 2846 rated for 7 bar at 83°C.

Pressure Ratings for SDR 11 C-PVC Hot Water Systems


Temperature	23°C	60°C	83°C	99°C
Pressure	28 Bar	14 Bar	7 Bar	5 Bar

The System is designed to 7 Bar pressure at 83°C, but provides a margin of safety should unusual conditions be encountered

C-PVC pipes

PART No.	SIZE	SP
100106	1/2"	25
100107	3/4"	25

Standard length is 10ft, with both ends plain, and must be used with PVC / C-PVC Clear Solvent Cement

Description	Part No.	Size (Inch)	SP	MC
Socket Union 	215606	1/2	10	20
	215607	3/4	10	10