




## Common Features

- Reliable performance at 25' depth to water or less
- Ready to Install 115 volt motor
- Pressure switch pre-wired to 30-50 PSI pressure setting
- Pump tank system pre-assembled and ready to install
- 7 gallon (15 gallon equivalent) pre-charged diaphragm tank
- 1" NPT suction and discharge
- Excellent self-priming capability after pump housing is initially filled (Check or foot valve required)



**Model 2802**  
3/4 HP  
1 Year Warranty

**Model 2800**  
1/2 HP  
1 Year Warranty



## Model 2802 / 2800

- Model 2802 energy-efficient 8.6 amp continuous duty motor
- Model 2802 maximum pumping capacity to 13 gallons per minute
- Model 2800 energy-efficient 7.2 amp motor continuous duty motor
- Model 2800 maximum pumping capacity to 12 gallons per minute



**Model 2802E**  
3/4 HP  
1 Year Warranty

**Model 2800E**  
1/2 HP  
1 Year Warranty



## Model 2802E / 2800E

- Model 2802E energy-efficient 8.6 amp motor continuous duty motor
- Model 2802E maximum pumping capacity to 13 gallons per minute
- Model 2800E energy-efficient 7.2 amp motor continuous duty motor
- Model 2800E maximum pumping capacity to 12 gallons per minute

## Performance

Model Number	HP	Warranty (Years)	Voltage	Pressure Switch		Gallons per Minute Pumped at Different Depths to Water*					Pressure Shut-off
				On	Off	5'	10'	15'	20'	25'	
2802 / 2802E	3/4	1	115	30	50	7.8	7.3	6.7	6.1	5.0	74 PSI
2800 / 2800E	1/2	1	115	30	50	5.1	4.5	4.1	3.5	3.1	63 PSI

\*All performances shown in gallons per minute at 40 PSI (pound per square inch) discharge pressure.